

Call: (609) 882-5250



Email: inquiry@gensullivan.com

<https://sullivansteelservice.com>

XD15NW		
AMS 5925, BMS 7-357		
High Hardness, Corrosion & Fatigue Resistance, Re-melted Martensitic Stainless; ESR		
Form	Dia (in)	Size (mm)
Wire	.098" - .744"	2.5mm - 18.9mm
Bar	.315" - 8.00"	8.0mm - 203.2 mm

XD16N		
AMS 5926		
Air-melt Version of XD15NW Stainless Steel; Air Melt		
Form	Dia (in)	Size (mm)
Wire	.217" - .512"	5.5mm - 13mm
Bar	.748" - 5.512"	19.0mm - 140.0mm
Flat Bar in .625"W x 6.0" T & 1.25"W x 1.50"T		

CX13VDW		
AMS 5719		
Carburizing Stainless Steel for Structural Applications; ESR		
Form	Dia (in)	Size (mm)
Bar	.787" - 6.00"	20mm - 152.4mm

NC310YW		
AMS 6499		
High Strength & Fatigue, Carburizable Alloy Steel; VIM-VAR		
Form	Dia (in)	Size (mm)
Bar	1.181" - 5.906"	30mm - 150mm

440C	
AMS 5630, 5880, & 5618	
High Carbon-Chromium Stainless Bearing & Blade Steel; Air Melt & VAR	
Form	Dia (in)
Bar (AM)	.25" - 6.50"
Bar (VAR)	.125" - 6.00"

GKHW		
UNS K24340		
High Temp Material for High Hardness & Excellent Fatigue Strength; ESR		
Form	Dia (in)	Size (mm)
Bar	5.512" & 6.299"	140mm & 160mm

GKPW/YW Bar		
AMS 6497 & 6498		
Deep Nitriding Steel with High Ductility & Fracture Toughness; ESR & VIM-VAR		
Form	Dia (in)	Size (mm)
Bar (ESR)	7.87"	200mm
Bar (Dbl Vac)	4.72" & 5.51"	120mm & 140mm

9310	
AMS 6265	
High Hardenability, Core Hardness and Fatigue Strength; VAR	
Form	Dia (in)
Bar	0.50" - 12.00"

M-50	
AMS 6490 & 6491	
High Temp Bearing Steel for Aerospace Applications; VIM-VAR	
Form	Dia (in)
Bar	.236" - 7.00"

8620	
ASTM 534 & AMS 6274	
Carburizing Bearing Steel in Bar & Tube; Air Melt	
Form	Dia (in)
Bar	.500" - 6.00"
Tube	1.772" - 10.50"

52100	
ASTM A295, AMS 6440, & 6444	
Standard High-Carbon Chromium Bearing Steel; Air Melt & VAR	
Form	Dia (in)
Bar (AM)	.130" - 15.75"
Tube	1.207" - 12.143"
Bar (VAR)	.236" - 6.00"

Nitriding 135M	
AMS 6471	
Nitriding Grade, High Case Hardness; VAR	
Form	Dia (in)
Bar	0.375"-3.00"